

Type 2008S Stainless Case 63mm Panel Builders Gauge



FEATURES

- Patented PowerFlex™ movement
- All stainless steel welded construction
- True Zero™ pointer indication
- Ventable offset fill plug
- MSL helium leak tested to 1×10^{-6} ATM - cc/sec
- CRN approved
- RoHS compliant
- Flange is welded to the case

Ashcroft offers the 2008S stainless steel panel gauge to panel builders in the oil and gas industry as well as food and pharmaceutical where performance, longevity, and appearance are critical requirements.

The 2008S utilizes many of the features of the Ashcroft Duralife 1009 and 1008S pressure gauges including the PowerFlex spring suspended movement design (helps prevent wear from vibration and pulsation); True Zero (which indicates actual zero pressure without the use of a dial pin installed at "0") and special laser welding procedures that assure system leak integrity.

You can also request **PLUS!™** Performance on the 2008S panel gauges and we will provide liquid filled gauge function without the concerns of temperature error and possible leaks associated with liquid filled gauges. Just ask for "XLL."

The 63mm panel mount flange allows for easy installation in new panels and to retrofit Ashcroft or other brand panel gauges.

PRODUCT SPECIFICATIONS

Ashcroft Type No.:	2008S
Size:	63mm
Case:	304SS
Ring:	304SS crimped, highly polished
Window:	Polycarbonate
Dial:	Black figures on white background, aluminum
Pointer:	Friction adjust, black, aluminum
Bourdon Tube:	316L stainless steel C-Shaped (vacuum-600 psi and compound) Helical (1000 psi-15000 psi)
Socket:	316L stainless steel
Movement:	300 series stainless steel, PowerFlex™, polyester segment, overload/underload stops
Connections:	1/4 NPT with four 7/16" wrench flats
Dials:	Vacuum, compound, 0-15 psi thru 0-15,000 psi. Also available in Kpa, bar, kg/cm²
Ranges:	Single or dual scale
Accuracy:	1.6% full scale ⁽¹⁾
Fill Plug:	Ventable and offset
Protection:	Nema 4X / IP65 plug sealed Nema 3 / IP54 plug vented

OPTIONAL FEATURES

Liquid fill:	Glycerin, silicone, halocarbon (includes throttle plug)
Dampening:	PLUS!™ Performance (XLL) (includes throttle plug)
Accuracy:	1% full scale (XAN)

⁽¹⁾ When these gauges are liquid filled the total gauge accuracy may be as much as 2.0%

FILL TYPE	Min/Max Temperature Limits		
	Ambient	Process	Storage
DRY (w/Polycarbonate Window)	-40/200°F	-40/250°F	-40/250°F
GLYCERIN	20/150°F	20/200°F	0/150°F
SILICONE	-40/150°F	-40/200°F	-40/150°F
HALOCARBON	-40/150°F	-40/200°F	-40/150°F

HOW TO ORDER (Typical example)

Dial Size: 63mm (63) 63
 Case Type: 2008 2008
 Tube and Socket Material: 316L SS S (L)
 Liquid Filled: (glycerin) leave blank if dry 02B
 Connection Size: 1/4 (02) XXX
 Connection Location: Lower Back (B) 100#
 Options: _____
 Range: 0/100 psi _____

All specifications are subject to change without notice.
 All sales subject to standard terms and conditions.
 © 2014 Ashcroft Inc. 08/14

Ashcroft Inc., 250 East Main Street, Stratford, CT 06614 USA
 Tel: 203-378-8281 • Fax: 203-385-0408
 email: info@ashcroft.com • www.ashcroft.com

Type 2008S Stainless Case 63mm Panel Builders Gauge

DIMENSIONS

All dimensions in brackets () are millimeters.
Dimensions are for reference only.

